

Formulation Additives by NAC Revision 2: Jun. 2024

NAC-DS-1065 S Safety Data Sheet

Wetting and Dispersing Additive (Solvent Based)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier used on the label: NAC-DS-1065 S

Recommended use of the chemical

and restriction on use:

Recommended use: industrial chemicals

Recommended use: for industrial use only

Unsuitable for use: Uses other than recommended

Details of the supplier of the safety

data sheet:

Company:

Noyan Afzon Chem, IRAN

Telephone: +98 2144787098

Other means of identification: Chemical family: Contains: additives, organic solvent

SECTION 2. HAZARDS IDENTIFICATION

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product:

Flam. Liq. 3 Flammable liquids.

Eye Dam./Irrit 2A Serious eye damage/eye irritation

Skin Corr./Irrit. 2 Skin corrosion/irritation

Resp. Sens. 1 Respiratory sensitization

Skin Sens. 1 Skin sensitization.

STOT SE 3 Vapors may cause Specific target organ

toxicity —single exposure

Aguatic Acute. 2 Hazardous to the aguatic environment -

acute

Aquatic Chronic. 2 Hazardous to the aquatic environment -

chronic

Label elements:

Pictogram:









Signal Word: Danger

Hazard Statement: H226 Flammable liquid and vapor.



Material Safety Data Sheet Formulation Additives by NAC Revision 2: Jun, 2024

| | H319 | Causes serious eye irritation. |
|--------------------------|------|--|
| | | |
| | H315 | Causes skin irritation. |
| | H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| | H317 | May cause an allergic skin reaction. |
| | H336 | May cause drowsiness or dizziness. |
| | H335 | May cause respiratory irritation. |
| | H401 | Toxic to aquatic life. |
| | H411 | Toxic to aquatic life with long lasting effects. |
| Precautionary Statements | | |
| (Prevention): | P280 | Wear protective gloves and eye/face protection. |
| | P261 | Avoidbreathing dust/fume/gas/mist/vapors/spray. |
| | P271 | Use only outdoors or in a well-ventilated area. |
| | P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| | P243 | Take action to prevent static discharges. |
| | P284 | In case of inadequate ventilation wear respiratory protection. |
| | P241 | Use explosion-proof electrical, ventilating and lighting equipment. |
| | P272 | Contaminated work clothing should not be allowed out of the workplace. |
| | P264 | Wash with plenty of water and soap thoroughly after handling. |
| | P242 | Use only non-sparking tools. |
| | P240 | Ground and bond container and receiving equipment. |



Material Safety Data Sheet Formulation Additives by NAC Revision 2: Jun, 2024

| Precautionary Statements (Response): | P312 | Call a POISON CENTER or doctor/physician if you feel unwell. |
|--------------------------------------|-----------------------|---|
| | P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Removecontact lenses, if present and easy to do. Continue rinsing. |
| | P304 + P340 | IF INHALED: Remove person to fresh air and keep comfortable forbreathing. |
| | P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| | | |
| | P333 + P311 | If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician. |
| | P362 + P364 | Take off contaminated clothing and wash it before reuse. |
| | P332 + P313 | If skin irritation occurs: Get medical advice/attention. |
| | P391 | Collect spillage. |
| | P337 + P311 | If eye irritation persists: Call a POISON CENTER or doctor/physician. |
| | P370 + P378 | In case of fire: Use foam or dry powder for extinction. |
| Precautionary Statements (Storage): | P403 + P235 | Store in a well-ventilated place. Keep cool. |
| | P233 | Keep container tightly closed. |
| | P405 | Store locked up. |
| Precautionary Statements (Disposal): | P501 | Dispose of contents/container to hazardous or special waste collection |

point.



Formulation Additives by NAC Revision 2: Jun, 2024

SECTION 3. FIRST AID MEASURES

Description of first aid measures:

General advice: Immediately remove contaminated clothing.

If difficulties occur after vapor/aerosol has been inhaled, remove to

fresh air and seek medicalattention.

If on skin: Wash affected areas thoroughly with soap and water. Seek medical

attention.

If in eyes: Immediately wash affected eyes for at least 15 minutes under

running water with eyelids held open, consult an eye specialist.

If swallowed: Immediately rinse mouth and then drink plenty of water, do not

induce vomiting, seek medicalattention. Never induce vomiting or

give anything by mouth if the victim is unconscious or

havingconvulsions.

Most important symptoms and effects,

both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (seesection 2) and/or in section 11.

Indication of any immediate medical

attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital

functions), no known specific antidote.

SECTION 4. FIREFIGHTING MEASURES

Extinguishing media: Suitable extinguishing media: Dry powder, foam

Special hazards arising from the

substance or mixture

Hazards during fire-fighting:

harmful vapors

Evolution of fumes/fog. The substances/groups of substances

mentioned can be released in case offire.

Advice for fire-fighters: Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

Further information: The degree of risk is governed by the burning substance and the

fire conditions. Contaminated extinguishing water must be disposed

of in accordance with official regulations.



Formulation Additives by NAC Revision 2: Jun. 2024

SECTION 5. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Use personal protective clothing. Breathing protection required. Can release flammable vapors. Wind direction should be noted. Avoid all sources of ignition: heat,sparks, open flame. Use antistatic

tools.

Environmental precautions: Contain contaminated water/firefighting water. Do not discharge into

drains/surface waters/groundwater.

Methods and material for containment

and cleaning up:

For large amounts: Pump off product.

For residues: Pick up with suitable absorbent material. Dispose of

absorbed material in accordancewith regulations.

SECTION 6. HANDLING AND STORAGE

Precautions for safe handling: Ensure thorough ventilation of stores and work areas.

Protection against fire and explosion:

Sources of ignition should be kept well clear. Take precautionary measures against static discharges. If delivered in plastic packing, highest permissible emptying temperature is 5 Kelvin below the

flash point.

Conditions for safe storage, including

any incompatibilities:

Further information on storage conditions: Keep container tightly

closed and in a cool place.

SECTION 7. EXPOSURE CONTROLS/PERSONAL PROTECTION

Advice on system design: Provide local exhaust ventilation to control vapors/mists.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapor/particulate

respirator.

Hand protection: Chemical resistant protective gloves.

Eye protection: Tightly fitting safety goggles (chemical goggles) and face shield.

Body protection: Impermeable protective clothing

General safety and hygiene measures: Handle in accordance with good industrial hygiene and safety

practice.

SECTION 8. PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid

Tel: (+9821) 44787098 Email: info@noyanafzon.com WhatsApp: (+98) 9056030635



Formulation Additives by NAC Revision 2: Jun, 2024

Odor: characteristic

Odor threshold: No applicable information available.

Color: Yellow

pH value: not applicable

Freezing point: not determined

Boiling point: 162 °C

Flash point: 40 °C

Flammability: Flammable

Lower explosion limit: 0.7 %(V)

Upper explosion limit: 7.5 %(V)

Autoignition: Not determined

Density: 0.9515 g/cm3 (20 °C)

Vapor pressure: : 5.0 hPa (20 °C)

Self-ignition temperature: 345 °C (not self-igniting)

Thermal decomposition: Not determined

Viscosity, dynamic: 110 mPa.s (20 °C)

Solubility in water: insoluble

Evaporation rate: Not determined

SECTION 9. STABILITY AND REACTIVITY

Reactivity: No hazardous reactions if stored and handled as

prescribed/indicated.

Corrosion to metals: No corrosive effect on metal.

Oxidizing properties: not fire-propagating

Chemical stability: The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions: No hazardous reactions when stored and handled according to

instructions. The product is chemically stable.

The product is chemically stable.

Conditions to avoid: See MSDS section 7 - Handling and storage.

Ncompatible materials: strong oxidizing agents, strong bases, strong acids

Tel: (+9821) 44787098 Email: info@noyanafzon.com WhatsApp: (+98) 9056030635



Formulation Additives by NAC Revision 2: Jun. 2024

SECTION 10. DISPOSAL CONSIDERATIONS

Waste disposal of substance: Dispose of in accordance with national, state and local regulations.

Container disposal: Uncontaminated packaging can be re-used. Packs that cannot be

cleaned should be disposed of inthe same manner as the contents.

WARNING: Empty containers may still contain hazardous residue.

SECTION 11. TRANSPORT INFORMATION

Land transport

TDG

Hazard class: 3
Packing group: III

ID number: UN 1866 Hazard label: 3, EHSM

Proper shipping name: RESIN SOLUTION

Sea transport

IMDG

Hazard class: 3 Packing group: III

ID number: UN 1866 Hazard label: 3, EHSM Marine pollutant: YES

Proper shipping name: RESIN SOLUTION (contains SOLVENT NAPHTHA)

Air transport

IATA/ICAO

Hazard class: 3
Packing group: III
ID number: UN 1866

Hazard label: 3

Proper shipping name: RESIN SOLUTION

END OF DATA SHEET

Tel: (+9821) 44787098 Email: info@noyanafzon.com WhatsApp: (+98) 9056030635