

Formulation Additives by NAC Revision 2: Jun. 2024

NAC- DF-2020 Safety Data Sheet Defoamer and Air Release Additive (Silicone Based)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier used on the label: NAC-DF 2020

Recommended use of the chemical

and restriction on use:

Recommended use:

additives for inks, varnishes or coatings,

Levelling agent

Recommended use: for industrial use only

Unsuitable for use: Uses other than recommended

Details of the supplier of the safety

data sheet:

Company:

Noyan Afzon Chem, IRAN

Telephone: +98 2144787098

Other means of identification: Chemical family: Contains: additives, organic solvent

SECTION 2. HAZARDS IDENTIFICATION

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product: Asp. Tox. 1 Aspiration hazard.

Flam. Liq. 3 Flammable liquids.

Skin Corr./Irrit. 2 Skin corrosion/irritation

Eye Dam./Irrit 2A Serious eye damage/eye irritation

Skin Sens. 1 Skin sensitization.

Aquatic Acute. 2 Hazardous to the aquatic environment -

acute

Aquatic Chronic. 2 Hazardous to the aquatic environment –

chronic

Label elements:

Pictogram:









Signal Word: Danger

Hazard Statement: H226 Flammable liquid and vapor.



Material Safety Data Sheet Formulation Additives by NAC Revision 2: Jun, 2024

	H319	Causes serious eye irritation.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H304	May be fatal if swallowed and enters airways.
	H401	Toxic to aquatic life.
	H411	Toxic to aquatic life with long lasting effects.
Precautionary Statements (Prevention):	P280	Wear protective gloves and eye protection or face protection.
	P261	Avoid breathing
		dust/fume/gas/mist/vapors/spray.
	P273	Avoid release to the environment.
	P280	Wear eye protection.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P243	Take action to prevent static discharges.
	P241	Use explosion-proof electrical, ventilating and lighting equipment.
	P272	Contaminated work clothing should not be allowed out of the workplace.
	P264	Wash contaminated body parts thoroughly after handling.
	P233	Keep container tightly closed.
	P240	Ground and bond container and receiving equipment.
	P242	Use only non-sparking tools.
Precautionary Statements (Response):	P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove
		contact lenses, if present and easy to do. Continue rinsing.



Formulation Additives by NAC Revision 2: Jun, 2024

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or physician.
P303 + P361 + P353	IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing.
	Rinse skin with water or shower.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P332 + P313	If skin irritation occurs: Get medical attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
P331	Do NOT induce vomiting.
P337 + P313	If eye irritation persists: Get medical attention.
P370 + P378	In case of fire: Use foam or dry powder for extinction.
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents and container to hazardous or special waste collection point.

SECTION 3. FIRST AID MEASURES

Precautionary Statements (Storage):

Precautionary Statements (Disposal):

Description of first aid measures:

General advice: Immediately remove contaminated clothing.

If difficulties occur after vapor/aerosol has been inhaled, remove to

fresh air and seek medical attention.

If on skin: Wash affected areas thoroughly with soap and water. Immediately

remove contaminated clothing. Wash contaminated clothing before

reuse. Seek medical attention.

If in eyes: Wash affected eyes for at least 15 minutes under running water

with eyelids held open, consult an eye

specialist. Remove contact lenses, if present. If symptoms persist,

seek medical advice.

If swallowed: Aspiration hazard Rinse mouth. Do NOT induce vomiting.

Immediately call a POISON CENTER/doctor.



Formulation Additives by NAC Revision 2: Jun, 2024

SECTION 4. FIREFIGHTING MEASURES

Extinguishing media: Suitable extinguishing media: Dry powder, foam

Unsuitable extinguishing media for safety reasons: No data

available.

Special hazards arising from the

substance or mixture

Hazards during fire-fighting:

Harmful vapors

Evolution of fumes/fog. The substances/groups of substances

mentioned can be released in case of fire.

Advice for fire-fighters: Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

Further information: The degree of risk is governed by the burning substance and the

fire conditions. Contaminated extinguishing water must be disposed

of in accordance with official regulations.

SECTION 5. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency

procedures:

Use personal protective clothing. Breathing protection required.

Can release flammable vapors. Wind direction should be noted. Avoid all sources of ignition: heat, sparks, open flame. Use

antistatic tools.

Environmental precautions: Contain contaminated water/firefighting water. Do not discharge into

drains/surface waters/groundwater.

Methods and material for containment

and cleaning up:

For large amounts: Pump off product.

For residues: Pick up with suitable absorbent material. Dispose of

absorbed material in accordance with regulations.

SECTION 6. HANDLING AND STORAGE

Precautions for safe handling: Ensure thorough ventilation of stores and work areas.

Protection against fire and explosion:

Sources of ignition should be kept well clear. Take precautionary measures against static discharges. If delivered in plastic packing, highest permissible emptying temperature is 5 Kelvin below the

flash point.



Formulation Additives by NAC Revision 2: Jun. 2024

Conditions for safe storage, including any incompatibilities:

Segregate from bases. Segregate from strong acids. Segregate from oxidants. Segregate from amines.

Further information on storage conditions: Small amounts of hydrogen may be evolved during shipping and storage. Avoid all sources of ignition: heat, sparks, open flame. Protect against moisture. Keep in a cool, well-ventilated place. Containers should be stored tightly sealed in a dry place.

Store as flammable liquid.

SECTION 7. EXPOSURE CONTROLS/PERSONAL PROTECTION

No occupational exposure limits known.

Advice on system design: No applicable information available.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapor/particulate

respirator.

Hand protection: Chemical resistant protective gloves.

Eye protection: Tightly fitting safety goggles (chemical goggles). Wear face shield if

splashing hazard exists.

Body protection: Impermeable protective clothing.

General safety and hygiene measures: Handle in accordance with good industrial hygiene and safety

practice.

SECTION 8. PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid

Odor: Alcohol-like

Odor threshold: No applicable information available

Colorless to yellowish

pH value: Not determined

Melting temperature: No data available

Boiling temperature: > 145 °C (1,013 hPa)

Boiling range: No data available

Sublimation point:.No applicable information available

Flash point: 42 °C (ASTM D93)

Tel: (+9821) 44787098 Email: info@noyanafzon.com WhatsApp: (+98) 9056030635



Formulation Additives by NAC Revision 2: Jun, 2024

Flammability: Flammable liquid and vapor. (derived from flash point)

Lower explosion limit: For liquids not relevant for classification and labelling. The lower

explosion point may be 5 - 15 °C below the flash point.

Upper explosion limit: For liquids not relevant for classification and labelling.

Autoignition: Not determined

Density: 0.92 g/cm3 (20 °C) (ISO 2811-3)

Relative density: 0.92

Vapor density: Not determined

Partitioning coefficient noctanol/

water (log Pow):

not applicable for mixtures

Self-ignition temperature: Not self-igniting

Thermal decomposition: Not determined

Solubility in water: Insoluble

Solubility (quantitative):No applicable information available.

Solubility (qualitative): Insoluble

Solvent(s): Organic solvents,

Molar mass:No applicable information available.

Evaporation rate: Not determined

SECTION 9. STABILITY AND REACTIVITY

Reactivity: Liberates hydrogen when in contact with following materials: water,

alcohols, acids, bases, metals, metal alloys not dangerous goods of class 4.3, since the rate of evolution of flammable gas formed in contact with water is below 1 liter per kilogram substance per hour.

Vapors may form explosive mixture with air.

Oxidizing properties: Not fire-propagating.

Chemical stability: The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions: Some hydrogen gas may be released. Hydrogen is flammable and

can form explosive mixtures with air.

The product is chemically stable.

Conditions to avoid: Avoid direct contact with water. Product may release hydrogen gas

- increased storage temperatures will accelerate this process. (cf.

chapter 7 for the storage temperature).



Formulation Additives by NAC Revision 2: Jun. 2024

Incompatible materials water, alcohols, strong acids, strong alkalis, strong oxidizing

agents.

Hazardous decomposition products: Decomposition products: Hazardous decomposition products: No

hazardous decomposition products if stored and handled as

prescribed/indicated.

Thermal decomposition: not determined.

SECTION 10. DISPOSAL CONSIDERATIONS

Waste disposal of substance: Dispose of in accordance with national, state and local regulations.

Container disposal: Uncontaminated packaging can be re-used. Packs that cannot be

cleaned should be disposed of in the same manner as the

contents.

WARNING: Empty containers may still contain hazardous residue.

SECTION 11. TRANSPORT INFORMATION

Land transport

USDOT

Hazard class: 3
Packing group: III

ID number: UN 1993 Hazard label: 3, EHSM

Proper shipping name: FLAMMABLE LIQUID, N.O.S.

Sea transport

IMDG

Hazard class: 3 Packing group: III

ID number: UN 1993 Hazard label: 3, EHSM Marine pollutant: YES

Proper shipping name: FLAMMABLE LIQUID, N.O.S.

Air transport

IATA/ICAO

Hazard class: 3
Packing group: III

ID number: UN 1993

Hazard label: 3

Proper shipping name: FLAMMABLE LIQUID, N.O.S.

END OF DATA SHEET