

NAC-AS 4600

Anti-settling and dispersing additive (Solvent Based)

Anti-settling and dispersing agent for solvent-based and solvent-free coatings prevents sedimentation and agglomeration of even heavy pigments.

Product Data

Composition: Solution of surface-active anionic compounds

Typical Properties:

Note: This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product.

Physical Form: clear, yellowish liquid
Active Content: 20-25%

Applications

Applications > Recommended for > Particularly Recommended: Coatings > solvent-based systems
> All kinds of resin systems

Recommended Levels:

Note: The properties and performance of the additive are greatly dependent upon the specific formulation in which it is utilized and, consequently, should always be tested (possibly at different treatment levels, temperatures, and/or time intervals) to verify performance before use.

Based on
Total formulation weight: 0.5-1%

Special Feature:

NAC-AS 4600 can be incorporated at any production stage of the paint, before or after the grind stage, doesn't impair gloss, flow, drying properties or adhesion, and doesn't influence the water resistance of finished paints.

Storage:

should be stored in a cool dry place, prevent from freezing

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.